

Teknik bilgiler model SW-W-SGO

Model	Ürün kodu	Kapasite 1. sarım kg	Kapasite üst sarım kg	Halat çapı mm	Halat çapı* mm	Kullanılabilir halat uzunluk. maks. sarım m	Her manivela donuşu için kaldırma mm	Gerekli manivela gücü daN	Halatsız ağırlığı kg
SGO 250	040251003	250	100	5	2,3	44	29	6	13
SGO 500	040252026	500	238	6	3,7	54	30	11	16
SGO 1000	040253006	1.000	500	9	4,5	46	21	10,6	26
SGO 1500	040253000	1.500	850	10	4,5	38	18	16	28
SGO 2000	030254002	2.000	1.100	13	4	37	8/16**	9/18**	60
SGO 3000	030255009	3.000	2.000	16	5	34,5	7/14**	12/24**	78
SGO 5000	030256013	5.000	3.300	20	4,5	33,8	8/16**	25,2/50,4**	105

* tavsiye edilen halat: DIN 3060 FE-znk 1770 sZ-spa

**1./2. hız

Boyutlar model SW-W-SGO

Model	SGO 250	SGO 500	SGO 1000	SGO 1500	SGO 2000	SGO 3000	SGO 5000
Ürün kodu	040251003	040252026	040253006	040253000	030254002	030255009	030256013
A, mm	238	269	302	302	410	436	436
B, mm	145	160	195	250	310	365	425
C, mm	100	115	141	178	196	251	316
D, mm	192	223	254	254	360	386	386
G, mm	106	107	110	111	137	137	137
H, mm	102	131	160	160	176	204	200
J Ø, mm	48	70	102	102	133	165	219
K Ø, mm	14	14	17	17	25	25	25
L Ø, mm	160	190	240	240	312	376	437
M, mm	191	221	266	278	383	443	495
N, mm	15	15	15	15	45	47	60
O, mm	354	384	429	441	-	-	-
P, mm	280	325	350	350	380	380	380
R, mm	171	192	264	306	420	527	604
S, mm	130	130	130	130	220	220	220

